

Secced Reach Plus 4 Kit TRI001

Head: SC-V20/100RP

Capacity of 0-32kg offer support for EFP configuration camera and studio application.

Improved drag system enhances smoothness of head movement, matching the quality of most famous brand. In addition, graded drag adjustment ensure fast change of tilt and pan drag.

Step-type counter balance system help operator to balance the camera in a minute without changing over and over to look for the right amount of counterbalance.

Quick release mechanism ensures operator to quickly mount or dismount the camera on the head.

All main parts are made with high quality CNC machine. It enhances parts machining precision, ensures high reliability and improves fluid head performance substantially.

In order to enhance rigidity of plastic parts, high quality hard plastic is adopted to manufacture all plastic parts of fluid heads, especially those control elements (brake level, clamp level etc.), which results in considerable high durability of SECCED fluid heads.

100mm ball head, compatible with heavy-duty 100mm tripod on the market.

Tripod: SC-EFP/CF100D

Speed Locking system ensures quick setup of tripods and operators can get it ready for work within a minute.

Equipped with off ground and ground spreader.

All plastic parts adopt the imported material, enhance the quality of spare parts and ensure high rigidity of tripods.



Reach Plus 4 Kit	
Weight	11.2 kg
Max Payload	32 kg
Height Range	81-180 mm
Bowl Diameter	100 mm
Transport Length	97 cm

Soft Case	
TRI110	Suitable for Reach Plus 4

Dolly	
TRI100	Suitable for 100-150 mm Tripods





Reach Plus 4 Kit Tripod Specifications

Head	
Weight	5.45 kg
Counter Balance	0-7 Steps
Sliding Range Plate	120 mm
Grades of Tilt Drag	0-7
Grades of Pan Drag	0-7
Tilt Range	-75°/+90°
Tripod Fitting	100mm

Payload

C.O.G (mm)	Min Payload (kg)	Max Payload (kg)
100	0.00	32.0
125	0.00	27.9
150	0.00	24.8
175	0.00	22.2
200	0.00	20.2

Tripod	
Weight <i>With Ground Spreader</i>	4.9 kg
Max Payload	90 kg
Height Range <i>With Ground Spreader</i>	57 - 161 cm
Height Range <i>With off Ground Spreader</i>	59-157 cm
Bowl Size	100 mm
Transport Length	78 cm
Extension	Double
Material	Carbon Fibre